MODEL 75 T-2000



Special calender for pieces or continuous fabrics, used for :

- Transfer printing
- Direct inks reactivation
- Thermosetting heatsetting

Versatile and polyvalent calender, developed for transfer printing of all the follows work conditions, according to required options:

- Printing paper in roll and material to be printed in roll
- Printing paper in roll and material to be printed in pieces
- Printing paper in sheets and material to be printed in pieces

1. Characteristics of printing cylinder:

1.1. Diameter : 200 mm (7,87"). 1.2. Width: 2.000 mm (78,74").

1.3. Working Width: 1.600 mm (62,99") / 1.800 (70,87").

2. Heating system and temperature control:

- 2.1. The cylinder is heated by one resistor (heating element) in a vacuum sealed oil bath, in complete absence of air and pressure. MONTI ANTONIO S.p.a system.
- 2.2. The temperature of the cylinder is set by a touch screen and is regulated by an electronic card. The temperature control is equipped with temperature alarm system and a limitation system of maximum temperature (230 °C).

3. Tension controls:

3.1. Tension control for printing material in roll:

Entry: brake with manual adjustment

Exit: winding with pneumatic device

3.2. Tension control for printing paper in roll:

Entry: disk brake with pneumatic adjustment

Exit: winding with pneumatic device

3.3. Tension control for protection paper:

Entry: disk brake with pneumatic adjustment

Exit: winding with pneumatic device

4. Other devices into machine:

- 4.1. Short front working table, 800 mm
- 4.2. Single motor
- 4.3. NOMEX felt with manual tension adjustment system and automatic felt-centering device

All data and technical features are purely indicative and subjected to changes without prior notice















MODEL 75 T-2000



4.4. Incorporated system of felt protection in case of black out and/or compressed air lack

5. Technical data:

- 5.1. Installed power: 14 kw/h
- 5.2. Average electric consumption: 9 kw/h
- 5.3. Compressed air pressure: 3 8 bar
- 5.4. Mechanic speed: 0.1 1.7 m/min
- 5.5. Overall dimensions (with front table and kit for back exit): width 3.110 mm (122,44"). length 2.080 mm (81,88"). height 1.385 mm (54,52").
- 5.6. Net weight: 1.300 kg
- 5.7. Machine produced according to CE rules
- 5.8. Customs tariff: 84 51 80 30

All data and technical features are purely indicative and subjected to changes without prior notice







